AMENDMENTS TO THE CLAIMS

Please amend the claims as indicated below.

- 1. (Currently amended) A caster wheel assembly for a wheeled device comprising:
 - a housing suitable for connection to a wheeled device;
 - a caster mounting assembly configured to mount a caster wheel for rotation;
- a caster bolt connected to the caster mounting assembly and inserted into the housing for rotation within the housing; and

a substantially flat damping insert having major faces oriented substantially vertically and applying a biasing force between the caster bolt and the housing to dampen the rotation of the caster bolt with respect to the housing, wherein the dampening insert is in contact with the caster bolt and the housing.

- 2. (Original) The caster wheel assembly of claim 1 including upper and lower bearings and a cylindrical spacer positioned between the bearings, and wherein the biasing force between the caster bolt and the housing consists of applying the biasing force between the spacer and the housing.
- 3. (Original) The caster wheel assembly of claim 2 in which the clamping insert is one or more discs positioned between the spacer and the housing.
- 4. (Original) The caster wheel assembly of claim 1 in which the lamping insert is a circular disc.
- 5. (Original) The caster wheel assembly of claim 1 in which the damping insert is comprised of a polymeric material.

BEST AVAILABLE COPY

6. (Currently amended) The caster wheel assembly of claim 1 A c 1ster
wheel assembly for a wheeled device comprising:
a housing suitable for connection to a wheeled device;
a caster mounting assembly configured to mount a caster wheel for rotation;
a caster bolt connected to the caster mounting assembly and inserted into the
housing for rotation within the housing; and
a substantially flat damping insert having major faces oriented substar tially
vertically and applying a biasing force between the caster bolt and the housing to
dampen the rotation of the caster bolt with respect to the housing, in which the
damping insert has a first stiffness along a first axis and a second, different stiffness
along a second axis that is perpendicular to the first axis, thereby enabling the damping
insert to be inserted into the caster wheel assembly in either of two orientations, with
the first orientation providing a first damping result and the second orientation
providing a different damping result.

- 7. (Original) The caster wheel assembly of claim 1 in which the damping insert is rectangular.
- 8. (Original) The caster wheel assembly of claim 1 in which the damping insert is readily removable and replaceable.
- 9. (Original) The caster wheel assembly of claim 1 in which the caster mounting assembly is a caster fork.
- 10. (Currently amended) A wheelchair having a frame, at least two drive wheels, and at least two caster wheels, each caster wheel being supported by a caster wheel assembly comprising:
 - a housing suitable for connection to the wheelchair;

a caster mounting assembly configured to mount a caster wheel for rotation;

a caster bolt connected to the caster mounting assembly and inserted it to the housing for rotation within the housing; and

a substantially flat damping insert having major faces oriented substantially vertically and applying a biasing force between the caster bolt and the housing to dampen the rotation of the caster bolt with respect to the housing, wherein the dampening insert is in contact with the caster bolt and the housing.

- 11. (Original) The wheelchair of claim 10 wherein the caster wheel assembly includes upper and lower bearings and a cylindrical spacer positioned between the bearings, and wherein the biasing force between the caster bolt and the housing consists of applying the biasing force between the spacer and the hot sing.
- 12. (Original) The wheelchair of claim 10 in which the damping in: ert is one or more discs positioned between the spacer and the housing.
- 13. (Original) The wheelchair of claim 10 in which the damping in sert is a circular disc.
- 14. (Original) The wheelchair of claim 10 in which the damping in sert is comprised of a polymeric material.
- 15. (Currently amended) The wheelchair of claim 10 A wheelchair having a frame, at least two drive wheels, and at least two caster wheels, each caster wheel being supported by a caster wheel assembly comprising:

 a housing suitable for connection to the wheelchair;

a caster mounting assembly configured to mount a caster wheel for rotation;

a caster bolt connected to the caster mounting assembly and inserted it to the housing for rotation within the housing; and a substantially flat damping insert having major faces oriented substantially vertically and applying a biasing force between the caster bolt and the housing to damp in the rotation of the caster bolt with respect to the housing, in which the damping insert has a first stiffness along a first axis and a second, different stiffness along a second axis that is perpendicular to the first axis, thereby enabling the damping insert to be inserted into the caster wheel assembly in either of two orientations, with the first orientation providing a first damping result and the second orientation providing a different damping result.

- 16. (Original) The wheelchair of claim 10 in which the damping insert is rectangular.
- 17. (Original) The wheelchair of claim 10 in which the damping insert is readily removable and replaceable.
- 18. (Original) The wheelchair of claim 10 in which the caster mour ting assembly is a caster fork.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

D	efects in the images include but are not limited to the items checked:
	□ BLACK BORDERS
	☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
	☐ FADED TEXT OR DRAWING
	☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
	☐ SKEWED/SLANTED IMAGES
	COLOR OR BLACK AND WHITE PHOTOGRAPHS
	GRAY SCALE DOCUMENTS
	☐ LINES OR MARKS ON ORIGINAL DOCUMENT
	☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
	Потитель

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.